

SCHULTE® SRW800 ROCK WINDROWER



Multi-Purpose 3-Point Hitch Windrower Breaks up Lumps, Levels the Ground



- 1 Variable hydraulic drum angle from 0° to 18°.
- 2 Windrows 2" to 25" rocks with ease, forming them into neat uniform rows.
- 3 Power is supplied to the windrower drum, via heavy duty PTO drive line which includes a slip clutch and shear bolt arrangement for protection against excessive shock loads.
- 4 The final drive chain is totally enclosed for longer service life.
- 5 The windrower drum is constructed of 8 5/8" (219mm) heavy wall tube.
- 6 Hard surfaced 5/8" thick (15.9mm) x 6" (152.4mm) long teeth are welded directly to the drum, resulting in problem-free operation.
- 7 Narrow, 8.5' transport width.

G O N U M B E R O N E . . . G O S C H U L T E !

Windrows Rocks & Debris With Ease

The **SRW800 Pivoting Rock Windrower** is designed to windrow small to medium rocks with ease, forming them into neat uniform rows ready for pickup by a Schulte Rock Picker. Roots, stumps, chips and other debris from land clearing operations can also be windrowed. As an added bonus, the windrower has roto-tilling action breaking up lumps and leveling the ground.

Rural municipalities and counties use the SRW800 Pivoting Rock Windrower to reclaim gravel from roadsides, proving the machine's rugged construction and durability. Save money by using your patrol to bring the gravel in off the shoulder and then using the Schulte SRW800 Pivoting Rock Windrower to spread the ridge smoothly and evenly.

SPECIFICATIONS

Weight (approximate)	1350 lbs. (613 kg)
Horsepower required	35 hp to 100 hp (30 - 60 kw)
Drum Width	88 5/8" (2215 mm)
Maximum Ground Speed	5 mph (8kph)
Recommended Ground Speed	2 mph (3 kph)
Drum Speed	102 rpm @ 540 input
Tires	16.5/6.5 x 8
Transport Width	8.5' (2591 mm)
Transport Length	67" (1702 mm)

Tractor Hydraulic requirements (at remote outlets)

5 gpm @ 1800 psi, dual remote outlet

Full one year warranty on materials and workmanship

Quality, Service, Performance



The **SRW800 Pivoting Rock Windrower** employs a side delivery frame allowing the operator to better control the size of windrows, regardless of rock conditions. The **SRW800** is the perfect tool for contractors, landscape companies, and farmers.

Power is supplied to the windrower drum via a heavy duty PTO drive line which includes a slip clutch and shear bolt arrangement for protection against excessive shock loads. The final drive chain is totally enclosed for longer service life. The windrower drum is constructed of 8 5/8" (219mm) heavy wall pipe, hard surfaced 5/8" (15.9 mm) thick teeth welded directly to the drum.



Heavy duty PTO drive line



Fully enclosed drive chain



Check out Schulte's high quality conveyor type and reel type rock pickers. These machines are your best choice for continuous picking of windrowed rocks.



RS320 "Jumbo"
Conveyor Type Rock Picker



2500 "Giant"
Reel Type Rock Picker

SCHULTE



Schulte Industries Ltd.

P.O. Box 70, Englefeld, Saskatchewan, Canada S0K 1N0

Tel: (306) 287-3715 Fax: (306) 287-3355

E-Mail: info@schulte.ca

Visit our Web site at: www.schulte.ca

Schulte is a registered trademark of Alamo Group Inc.

Schulte Industries Ltd. reserves the right to change the design, specification of its products without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.



ISO 9001

PRINTED IN CANADA

PREPARED by NELSON GRAPHIC DESIGN

200909